



OZZ WR2 65

The OZZ WR2 65 is engineered to deliver exceptional visibility and enhanced safety. Features a powerful flood beam with an impressive actual output of 2180 lumens and a 1 lux reach of 65 meters, ensuring safer operation in demanding conditions. A red tail position light adds a striking visual element, while the integrated E-approved LED warning light provides an invaluable safety feature for alerting nearby traffic in low-visibility environments. Built with a durable aluminum chassis and a tough polycarbonate lens, the light bar is designed to perform reliably in any weather. Its IP68/69K-rated protection ensures resistance to both dust and water. Backed by a three-year warranty, the OZZ WR2 65 combines high-quality construction with advanced functionality, making it an ideal choice for private users, professional drivers, and off-road enthusiasts alike.

| | | | |
|----------------------------|---|--------------------------------------|----------------------------------|
| Art. no. | 88507 | Color LED | White, red |
| Pcs LED | 22 | Connection | 4-pin DT male + female + 1 cable |
| Voltage | 10-32V DC | Cable lenght (mm) | 1000 (800+200) |
| Theoretical effect | 40W | Material bracket | Stainless steel |
| Actual effect | 36W (12V DC), 36W (24V DC) | Material housing | Aluminum |
| Nominal current | 3A (12V DC), 1,5A (24V DC) | Material lens | Polycarbonate |
| Functions | Reversing light, Warning light, Work light | Lenght (mm) | 164 |
| Theoretical lumen | 3600 | Depth (mm) | 70 |
| Actual lumen | 2180 | Height (mm) | 45 |
| 1 lux @ | 65 m | Height including bracket (mm) | 60 |
| Kelvin | 5000K | Operating temperature | -40°C - +60°C |
| IP-class | IP68/IP69K | E-mark approval | ECE R23, R65, R148 |
| Beam pattern | Flood | EMC | ECE R10 |
| Flash light pattern | Double flash | Pcs in master box | 20 |
| Position light | Red position light | EAN | 7350166880583 |
| Color housing | Black | Warranty | 3 years |
| RAL color | RAL9011 | | |
| Color lens | Clear | | |

